

# SUB ONE

## Product sheet

Sub One is a subwoofer composed of two 8" (20cm) Slatefiber cone woofers, manufactured in France by Focal. With a total RMS power of 200W, it covers a frequency band from 32Hz to 120Hz. Sub One offers great dynamics whilst maintaining low distortion. Designed with a focus on its width and front vents, Sub One integrates easily into a room, along a wall or under a desk.



Type	Sub One
Frequency response (+/-3dB)	32Hz - 120Hz
Maximum SPL	114dB SPL (peak @ 1m)
Inputs	Left, Right, LFE Electronically balanced / 110kOhms 3-point female XLR Variable
Outputs (to satellites)	Left + Right 3-point male XLR in parallel on inputs
Amplification	2 x 100W RMS, D-class
Internal signal processing and functions	Left + Right mono summation 60Hz or 90Hz high-pass crossover Adjustable low-pass crossover, 24dB/octave Phase adjustment Polarity
User controls	Subwoofer level adjustment (sensitivity) Low-pass crossover cut-off frequency adjustment Phase adjustment Polarity inverter External mute (controlled by a pedal)

Indicators (LED)	Power Defeat
Power supply	Universal detachable IEC inlet power cord
Subwoofer	2 x 8" (20cm) long-excursion Focal speaker drivers with "Slatefiber" cone
Construction	7/8" (22mm) MDF panel with internal braces
Finish	Dark grey vinyl
Dimensions (HxWxD)	18 <sup>3/4</sup> " x 11 <sup>3/4</sup> " x 19 <sup>3/4</sup> " (475x310x520mm)
Weight	40.8lbs (18.5kg)

